465N-6407 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF3	DF2	DF1	FC	PF1	PF2	PF3
DC						PC

FLASH PATTERN: TOW APPLICATION (LOOP CUT)

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION
		FRONT / CORNER STROBES
0	NONE	NONE
1	ORG	DF3 & PF3 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMULTANEOUS (6 PULSES PER BURST) DF1 ALTERNATES WITH PF1 DC ALTERNATES WITH PC (3 PULSES PER BURST)
2	ORG & BLU	SAME AS MODE 1
3	ORG & WHT/BLK	SAME AS MODE 1
4	ORG & BLU & WHT/BLK	SAME AS MODE 1
5	BLU	NONE
6	WHT/BLK	NONE
7	BLU & WHT/BLK	NONE

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
BROWN	FC (TAKEDOWN)

NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.