465N-7508 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF4 DF3 DF2 DF1 FC PF1 PF2 PF3 PF4
DC PC

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION
		FRONT / CORNER STROBES
1	ORG	DF1 ALTERNATES WITH PF1 (4 PULSES PER BURST)
2	ORG & BLU	DF4 & PF4 SIMULTANEOUS AND ALTERNATE WITH DF3 & PF3 SIMULTANEOUS (6 PULSES PER BURST) PF1 & DF1 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMUTANEOUS (6 PULSES PER BURST)
3	ORG & WHT/BLK	DF4 & PF4 SIMULTANEOUS AND ALTERNATE WITH DF3 & PF3 SIMULTANEOUS (6 PULSES PER BURST) PF1 & DF1 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMUTANEOUS (6 PULSES PER BURST) DC ALTERNATES WITH PC (3 PULSES PER BURST)
4	ORG & BLU & WHT/BLK (**OPTIONAL PREEMPTION**)	SAME AS MODE 3 NOTE: EXCEPT LAMPS DF4, DF3, PF3 & PF4 OPERATE IN **PREEMPTION** FLASH RATE, IF THE PRE OPTION IS ORDERED AND FACTORY INSTALLED

* NOTE: PREEMPTION CAN BE ACHIEVED WITH EITHER OPTION /PRE OR /PRE2-1C

CONTROL WIRES FOR OPTIONAL HALOGEN

CONTROL WIRE ACTIVATED	**HALOGEN LAMP**
GRY	(SPLIT TAKEDOWN)
YEL	(SPLIT TAKEDOWN)

CONTROL WIRES FOR OPTIONAL PREEMPTION

CONTROL WIRE ACTIVATED	**STROBE LAMPS**
BRN	PARKING BRAKE OVERRIDE

CONTROL WIRES FOR OPTIONAL PRE2-1C

CONTROL WIRE ACTIVATED	**DF1 STROBE LAMP**
BRN	ACTIVATE PREEMPTION EMITTER

CONTROL WIRES FOR OPTIONAL ICC MARKER LIGHTS

CONTROL WIRE ACTIVATED	
BRN/WHT	ACTIVATE ICC MARKER LIGHTS

NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.