465N-8810-0082 FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF5 DF4 DF3 DF2 DF1 PF1 PF2 PF3 PF4 PF5
DC PC

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION FRONT / CORNER STROBES
0	NONE	NONE
1	ORG	DF5 ALTERNATES WITH PF5 DF4 & PF4 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMUTANEOUS DF3 ALTERNATES WITH PF3

CONTROL WIRES FOR OPTIONAL ICC MARKER LIGHTS

CONTROL WIRE ACTIVATED	HALOGEN LAMP
BRN/WHT	ALL 5 ICC LIGHTS

CONTROL WIRES FOR HALOGEN CORNER LAMPS

CONTROL WIRE ACTIVATED	HALOGEN LAMP	
GRY	DC	45-DEGREE CORNER
YEL	PC	45-DEGREE CORNER

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED	HALOGEN LAMP	
RED/WHT	DF1	TAKEDOWN
BRN	PF1	TAKEDOWN

Or **OPTIONAL Dual Mode Halogen Operation**

RED/WHT	DF1 & PF1	FRONT FLASHER
BRN	DF1 & PF1	STEADYBURN

NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.