

# 930H-4805-0064 FLASH PATTERN

## LIGHTBAR LAMP CONFIGURATION



MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY HALOGENS	FRONT / CORNER HALOGENS
0	NONE	NONE	NONE
FACTORY DEFAULT (INBOARD/OUTBOARD)	ORANGE (WIRED TO PIN 2 OF 930H-16)	DR2 & RCL, PR2 & RCR & DA SIMULTANEOUS AND ALTERNATE WITH DR1, PR1 & PA SIMULTANEOUS	DF2 & PF2 SIMULTANEOUS AND ALTERNATE WITH DF1 & PF1 SIMULTANEOUS DC ALTERNATES WITH PC
ALTERNATE PATTERN 1	ORANGE (WIRED TO PIN 6 OF 930H-16)	DR2 & RCL, DR1 & DA SIMULTANEOUS AND ALTERNATE WITH PR2 & RCR, PR1 & PA SIMULTANEOUS	DF2 & DF1 SIMULTANEOUS AND ALTERNATE WITH PF2 & PF1 SIMULTANEOUS DC ALTERNATES WITH PC
ALTERNATE PATTERN 2	ORANGE (WIRED TO PIN 7 OF 930H-16)	DR2 & RCL, DR1, PR1, PR2 & RCR, PR1, DR1, REPEAT DA ALTERNATES WITH PA	DF2, DF1, PF1, PF2, PF1, DF1, REPEAT DC ALTERNATES WITH PC

## CONTROL WIRES FOR OPTIONAL HALOGENS

### CONTROL WIRE ACTIVATED

BLUE  
WHITE/BLACK

### HALOGEN LAMP

FC (TAKEDOWN)  
DA & PA (ALLEYS)

**NOTE: The 930H-4805 lightbar comes wired for the FACTORY DEFAULT flash pattern.**