

930NH-7208/PRE FLASH PATTERN

LIGHTBAR LAMP CONFIGURATION

DF4	DF3	DF2	DF1	PF1	PF2	PF3	PF4
DC							PC
DA							PA
DR4	DR3	DR2	DR1	PR1	PR2	PR3	PR4

MODE	CONTROL WIRES ACTIVATED	LAMP OPERATION	
		REAR / ALLEY STROBES & HALOGENS	FRONT / CORNER STROBES & HALOGENS
1	ORG (ALL ON) *PREEMPTION*	<u>STROBES</u> DR4, PR4 & DA SIMULTANEOUS AND ALTERNATE WITH DR2, PR2 & PA SIMULTANEOUS <u>HALOGENS</u> DR1 & DR3 SIMULTANEOUS AND ALTERNATE WITH PR1 & PR3 SIMULTANEOUS	<u>STROBES</u> DF4 & PF4 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMULTANEOUS (6 PULSES PER BURST) DC ALTERNATES WITH PC (3 PULSES PER BURST) <u>PREEMPTION SIGNAL</u> (HIGH PRIORITY) DF1 ALTERNATES WITH PF1 (HIGH PRIORITY FLASH RATE) <u>HALOGENS</u> DF3 ALTERNATES WITH PF3
2	ORG & BRN/WHT (ALL ON) PARKING BRAKE OVERRIDE	<u>STROBES</u> SAME AS MODE 1 <u>HALOGENS</u> SAME AS MODE 1	<u>STROBES</u> SAME AS MODE 1 <u>NON-PREEMPTION SIGNAL</u> (PARKING BRAKE OVERRIDE) DF1 ALTERNATES WITH PF1 (STANDARD FLASH RATE) <u>HALOGENS</u> SAME AS MODE 1

CONTROL WIRES FOR OPTIONAL HALOGENS

CONTROL WIRE ACTIVATED

BROWN
GRAY
YELLOW

HALOGEN LAMP

DF2 & PF2	SPLIT TAKEDOWN
DA	DRIVER ALLEY
PA	PASSENGER ALLEY

**NOTE: GREEN control wire activates high intensity to strobes.
Apply +12vdc to appropriate control wire to activate desired function.**