

# FIRE ALARM PULL STATIONS



- Weather proof
- Single or Dual Action
- Break Glass
- Lift and Pull
- Terminal strip or Pigtail connection
- 9 different colors
- Custom lettering available in any language
- Single or Double contact

## RMS-WP Series

Weather proof fire alarm pull stations

Tomar weatherproof manual pull stations are made entirely in the U.S.A. of the finest materials and workmanship available. The low profile design and smooth edges offer an attractive yet functional design. The high-strength metal die-cast alloy will provide many years of dependable service in even the harshest industrial environments. All components are pre-painted or have plated surfaces to inhibit corrosion.

Tomar Single Action manual pull stations are activated quickly and easily by pulling down the T-handle. Dual Action Lift and Pull and Break Glass are available to minimize accidental or malicious alarm activations.

Electrically the Tomar pull station is unbeatable with 10 amp snap action switch offered in all possible contact arrangements (including gold contacts). Tomar pull stations can be used with or without the included glass rod, with replacement requiring no special tools.

## RMS-WP Ordering Information

Model	Description
RMS-PWP	SPST with Pigtail connection
RMS-TWP	SPST with Terminal strip connection
RMS-2WP	SPST with Terminal strip connection.
RMS-WP-LP	SPST with Terminal strip connection / Lift and Pull
RMS-WP-BG	DPDT with Terminal strip connection / Break Glass

## Specifications

Item	Description
UL Rating	Weather proof
Contacts	D.P.D.T. (double pole double throw)
Contact Rating	10 amps @ 125/250 VAC.
Wire AWG	12 to 22 AWG
Wiring	Terminal block or pigtail
Construction	Metal
Mounting	Hardware & instructions included
Dimensions Single Action	Width - 3.2in Height - 4.75in Depth - 3.25in Weight - 2.02 lb
Dimensions Dual Action, Lift and Pull (LP)	Width - 3.2in Height - 4.75in Depth - 3.25in Weight - 2.2 lb
Dimensions Dual Action, Break Glass (BG)	Width - 3.2in Height - 4.75in Depth - 3.95in Weight - 2.6 lb

### Options – please add at time of order

KL Key lock

### Accessories

GR Replacement glass rods  
 GP Replacement glass  
 LP Lift and Pull cover  
 DAH Break glass adapter

### How to Order:

- Specify model number
- Specify options, special lettering, and color if other than Red

### Architect and Engineer Specifications

The manual pull station shall be Tomar series RMS or approved equal. The pull station shall be weather proof and UL listed. The pull station must be made of high-strength metal die-cast alloy. Single action model activation shall be by T-handle pull-down function. Dual action model activation shall be by Lift and Pull cover, or Break Glass action. The pull station must be able to be activated either with or without a glass rod, which must be field-replaceable and requiring no special tools. The pull station must be available with either single or double pole switch, and with either pigtail or terminal block design